

# 760237066 | CPP-6A-SDDM-SL-1U-48

Discrete Distribution Module Panel, Cat 6A, SL, STP, 1U, 48 port



## Product Classification

Regional Availability	Asia   Australia/New Zealand   EMEA   Latin America   North America
Portfolio	CommScope®
Product Type	RJ45 patch panel
Product Series	SL Series

## General Specifications

ANSI/TIA Category	6A
Cable Type	Shielded
Color	Black
Growth Configuration	Fully loaded
Modules, quantity	4
Panel Style	Straight
Rack Type	EIA 19 in
Rack Units	1
Total Ports, quantity	48
Transmission Standards	ANSI/TIA-568-D.2   ISO/IEC 11801 Class EA
Wiring	T568A   T568B

## Dimensions

Height	44.45 mm   1.75 in
Width	482.6 mm   19 in
Depth, with cable management	119.38 mm   4.7 in
Compatible Diameter Over Dielectric, maximum	1.168 mm   0.046 in

# 760237066 | CPP-6A-SDDM-SL-1U-48

**Compatible Diameter Over Dielectric, minimum** 0.762 mm | 0.03 in

## Electrical Specifications

**Current Rating at Temperature** 1.5 A @ 20 °C | 1.5 A @ 68 °F

**Dielectric Withstand Voltage, RMS, conductive surface** 1,500 Vac @ 60 Hz

**Dielectric Withstand Voltage, RMS, contact-to-contact** 1,000 Vac @ 60 Hz

**Insulation Resistance, minimum** 500 MOhm

## Material Specifications

**Material Type** High-impact, flame retardant, thermoplastic | Powder-coated steel

## Environmental Specifications

**Operating Temperature** -10 °C to +60 °C (+14 °F to +140 °F)

**Storage Temperature** -40 °C to +70 °C (-40 °F to +158 °F)

**Relative Humidity** Up to 95%, non-condensing

**Flammability Rating** UL 94 V-0

**Safety Standard** RCM | UL | cUL

## Packaging and Weights

**Included** Modular jacks (48)

**Packaging quantity** 1

## Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RCM	Compliant to electrical safety & telecommunications requirements
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant

