

# + Mouse Lenovo

PN: MOUSE00



- Interface USB
- Resolução de 1000 DPI
- Óptico (sem esfera)
- Compatível com toda linha Lenovo
- Ambidestro
- Botão Scroll para rolagem

## MOUSE Lenovo USB - Overview



Foto meramento illustrativa

### Overview

Experience the performance of high-definition tracking, full programmability and the superior comfort of the new Lenovo Mouse. **Optical technology delivers extraordinary accuracy and more responsiveness than traditional mice**, resulting in smoother tracking on virtually any surface. A tilting scrollwheel allows the user to scroll through documents and webpages both horizontally and vertically. Designed for both right- and left-handed use, the Lenovo Mouse offers the ultimate in all-day comfort, precision and performance.

- **1000 dpi resolution**
- Fully programmable tilting scrollwheel and buttons
- Ambidextrous design for both right- and left-handed users
- Full-speed USB connection
- Full-featured Lenovo Mouse software suite
- Exclusive soft-to-the-touch metallic black finish

### Tech Specs

Ship Group **Enhanced Optical** USB Mouse

**Agency Approvals & Certifications** EN 60825-1, EN 60950, BSMI, C-ick, CISPR-22 Class B, RoHS, CUL, TUV, VCCI, FCC Class B - Part 15, IEC 60825-1, IEC-60950-1 (CB Certificate and CB Test Report), MIC (Korea), EN 55022, EN 55024

Maximum Operating Humidity	80
Maximum Operating Humidity Units	%
Minimum Operating Humidity	8
Minimum Operating Humidity Units	%
Maximum Operating Temperature	40
Maximum Operating Temperature Units	C
Minimum Operating Temperature	0
Minimum Operating Temperature Units	C
Depth Metric	115
Depth	115mm
Depth Metric Units	mm
Depth (US)	4.5in
Height Metric	36
Height	36mm
Height Metric Units	mm
Height (US)	1.43in
Max Operating Humidity + Units	80%



Min Operating Humidity + Units	8%
Max Operating Temperature + Units	40C
Min Operating Temperature + Units	0C
Weight US	0.2
Weight US Units	lbs
Weight Metric	0.095
Weight Metric Units	Kg
Width Metric	61
Width	61mm
Width Metric Units	mm
Width (US)	2.4in
Warranty Type	Customer Replaceable Unit

