

[How to Buy](#)

[Premier Login](#)



[Browse](#)

[Support](#)

[For Work](#)

[Dell Monitors](#)

[Dell Monitors](#)

[Dell 22 Monitor: P2217H](#)

Dell 22 Monitor: P2217H

More productive than ever.

Dell 22 Monitor | P2217H brings greater productivity to the workplace with added user comfort and convenience.



Display

Diagonal Viewing Size

54.61 cm

21.5 Inches

Preset Display Area (H x V)

476.06 mm x 267.79 mm

18.74" x 10.54"

127484.10 mm² (197.6 inches²)

Panel Type

In-Plane switching Technology

Display Screen Coating

Antiglare with 3H hardness

Maximum Preset Resolution

1920 x 1080 at 60Hz

Viewing Angle

(178° vertical / 178° horizontal)

Pixel Pitch

0.248mm x 0.248 mm

Pixel Per Inch (PPI)

102

Contrast Ratio

1000: 1 (typical)

4 Million: 1 (Dynamic)

Aspect Ratio

(16:9)

Backlight Technology

LED

Brightness

250 cd/m² (typical)

Response Time

6ms (gray to gray)

Wireless Charging Feature

NA

G-SYNC Support

NA

Adjustability

Height-adjustable stand (130mm),

Tilt (-5° to 21°)

Swivel (45° to 45°)
Pivot (90° clockwise)
Built in cable-management

PbP / PiP

PbP (No)

PiP (No)

Daisy Chain Availability

No

Dell Display Manager Compatibility

Yes

Remote Asset Management

Yes, via Dell Command |Monitor

Color Support

Color Gamut (typical): 82% (CIE 1976), 72% (CIE 1931)

Color Depth: 16.7 Million colors

Color Calibration SDK SW

No

Color Calibration with X-rite colorimeter

No

Flat Panel Mount Interface

VESA (100 mm)

Audio Output

Optional Soundbar - (AC511)

Connectivity

1 x DP (ver 1.2)

1 x HDMI (ver 1.4)

1 x VGA

1 x USB 3.0 port - Upstream

2 x USB 3.0 ports - Side

2X USB 2.0 – bottom.

Built-in Devices

USB3.0 super-Speed Hub (with 1 x USB upstream port, 2 x USB3.0 and 2 x USB2.0 downstream ports)

Security

Security lock slot (cable lock sold separately)
Anti-theft stand lock slot (to panel)

Dimensions

Height with stand (Compressed ~ Extended)

354.4 mm ~ 477.8 mm
18.81" ~13.95"

Width

498.9 mm
19.64"

Depth

180.0mm
7.09 inches

Height without stand

297.3 mm
11.70"

Width without stand

498.9 mm
19.64"

Depth without stand

50.3mm
1.98"

Weight (panel only - for VESA mount)

2.81 kg
6.18 lb

Weight (with packaging)

6.86 kg
15.09 lb

Power

Voltage Required

100 to 240 VAC / 50 or 60 Hz \pm 3Hz / 1.5 A (typical)

Power Consumption (Operational)

17W (typical) / 37W (maximum) / 50.6 kWh (Energy Star)

Power Consumption Stand by / Sleep

Less than 0.3W

Environmental**Temperature Range**

Operating: 0° to 40°C (32° to 104°F)

Non-operating: -20° to 60° (-4° to 140° F)

Humidity Range

Operating: 10% to 80% (non-condensing)

Non-Operating: 5% to 90% (non-condensing)

Altitude

Operating: 5,000 m (16,400 ft) max

Non-Operating: 12,191 m (40,000 ft) max

Warranty

3-Year Advanced Exchange Service and Premium Panel Guarantee.

Regulatory**Compliant Standards**

ENERGY STAR

EPEAT Gold

TCO Certified Displays

RoHS Compliant

Product Safety, EMC and Environmental Datasheets

Dell Regulatory Compliance Home Page

Dell and the Environment

What's Included

Monitor with stand

Power cable
1 x DP Cable
1 x VGA Cable
1 x USB 3.0 upstream cable (enables the USB port on the monitor)
Drivers and documentation media
Quick setup guide
Safety Information

Ultrabook, Celeron, Celeron Inside, Core Inside, Intel, Intel Logo, Intel Atom, Intel Atom Inside, Intel Core, Intel Inside, Intel Inside Logo, Intel vPro, Itanium, Itanium Inside, Pentium, Pentium Inside, vPro Inside, Xeon, Xeon Phi, and Xeon Inside are trademarks of Intel Corporation in the U.S. and/or other countries.

[P21-CS02](#)