

iDS-6708NXI-I/8F(B) DeepinMind SERIES NVS



Key Features


- Powerful face pictures library management
- Face pictures comparison and alarm linkage actions
- More precise face recognition and analytics based on deep learning algorithm
- Up to 8-ch 12 MP IP cameras can be connected
- Configurable arming time of alarm input/output
- Audio alarm, notifying surveillance center, sending email and alarm output
- Supports multiple VCA (Video Content Analytics) events
- Easy network access via Hik-Connect
- Access via multi-browsers such as IE, Firefox, Chrome, Safari, etc.
- 2 Gigabit Ethernet network interfaces



Specifications

Model		iDS-6708NXI-I/8F(B)
Face detection and analysis	Face picture library	16 libraries
		100, 000 pictures
	Face picture comparison alarm	8-ch face pictures comparison alarm; Alarm linkage actions: recording, audio warning, notify surveillance center, send email
Video/Audio output	VGA output	2 × VGA
	HDMI output	2 × HDMI
	Audio output	2-ch, RCA (Linear, 1 KΩ)
Video/Audio input	IP video input	8-ch
	Incoming/Outgoing bandwidth	256 Mbps/200 Mbps
Decoding	Decoding format	H.265/H.265+/H.264/H.264+/MPEG4
	Live view/playback resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
	Synchronous playback	8-ch
	Capability	16-ch @ 1080p
Hard disk	Hard disk	1, built-in 2.5-inch 2 TB SATA hard disk
External interface	Two-way audio	1-ch, RCA (2.0 Vp-p, 1 kΩ)
	Network interface	2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces
	Serial interface	RS-232; RS-485
	USB interface	Rear panel: 1 × USB 3.0, 1 × USB 2.0
	Alarm in/out	16/4
General	Power supply	12 VDC
	Total power	40 W
	Consumption (without hard disk)	≤ 30 W
	Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Working humidity	10 to 90 %
	Dimensions (W × D × H)	315 × 65 × 240.8 mm (12.4"× 2.6" × 9.5")
	Weight	≤ 3 kg (6.6 lb)

Physical Interfaces



Index	Description	Index	Description
1	LINE IN	7	LAN1 and LAN2 Interface
2	RS-232 Interface	8	AUDIO OUT
3	VGA Interfaces	9	HDMI Interfaces
4	Power Supply	10	USB 3.0 Interface
5	SW Dial	11	Alarm In/Alarm Out and RS-485 Interface
6	USB 2.0 Interface	12	GND

Available Models

iDS-6708NXI-I/8F(B)

Distributed by

HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-8690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216) 521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com